



FIRETEX J120

PRODUCT TECHNICAL DATA

Revised 10/2013 Issue 3

PRODUCT INFORMATION

PRODUCT DESCRIPTION	PACKAGE
<p>FIRETEX J120 JET FIRE SCRIM CLOTH</p> <p>A high temperature jet fire resistant fabric scrim cloth</p>	<p>Pack Size: Supplied on rolls that are nominally 50m long and 1m wide.</p> <p>Shelf Life: Minimum 2 years from date of supply</p>
RECOMMENDED USE	HEALTH AND SAFETY
<p>As a high temperature jet fire resistant fabric scrim cloth designed to reinforce the insulation 'char' developed when FIRETEX M90 reacts in a fire. Suitable for use in hydrocarbon pool fires or jet fires for the protection of structural steelwork, process vessel and support structures, and on deck and bulkhead panels.</p> <p>Installation to be in accordance with the FIRETEX M90 application manual and per certification requirements.</p>	<p>Not Hazardous</p>
ENDORSEMENTS	WARRANTY
<p>Approved by Lloyds Register of Shipping Approved by Det Norske Veritas Approved by Bureau Veritas Approved by American Bureau of Shipping Approved by Bundesanstalt fur Materialforschung und-prufung Approved by the Head of the Netherlands Shipping Inspection Approved by Underwriters Laboratory for UL1709 external use</p>	<p>Any person or company using the product without first making further enquiries as to the suitability of the product for the intended purpose does so at their own risk, and Sherwin-Williams can accept no liability for the performance of the product, or for any loss or damage arising out of such use.</p> <p>The information detailed in this Data Sheet is liable to modification from time to time in the light of experience and of normal product development, and before using, customers are advised to check with Sherwin-Williams, quoting the reference number, to ensure that they possess the latest issue.</p>
RECOMMENDED APPLICATION METHODS	
<p>Installed by hand layup in accordance with the 'FIRETEX M90 Application Manual'</p>	
PRODUCT CHARACTERISTICS	
<p>Colour Availability: Black</p> <p>VOC: None</p>	
RECOMMENDED THICKNESS	
<p>Cloth thickness is 0.4mm ± 5%. Nominal weight is 170g/m² ± 5%</p>	
PRACTICAL APPLICATION RATES - MICRONS PER COAT	
<p>Required quantity of cloth will depend on the size and shape of the structure to be fire protected.</p> <p>FIRETEX J120 cloth is supplied in rolls nominally 50m long and 1m wide. Cut cloth to size and install in accordance with the 'FIRETEX M90 Application and Use Manual'</p>	
SURFACE PREPARATION	
<p>FIRETEX J120 is intended to be encapsulated within wet applied FIRETEX M90. See 'FIRETEX M90 Application Manual' for details.</p>	